



„Innovationen im Holzbau“

**GH column base type T05 extra strong on concrete**

ETA-16/0550



0769

**General**

Post supports are approved for service classes 1, 2 and 3.

**Timber column**

Softwood, C24 or higher strengths

Glulam

Minimum dimensions **min w x min h** see structural calculations table

**Timber column fasteners**

- Wood screws
  - Ø8x70 -  $l_{ef} \geq 50$  mm
  - Ø10x120 -  $l_{ef} \geq 100$  mm
  - Ø10x60, Ø4x60 -  $l_{ef} \geq 40$  mm
  - Ø12x80 -  $l_{ef} \geq 60$  mm
- $l_{ef}$  = minimum thread lengths
- If screws with thread length  $l_{ef}$  greater than 100 mm are used, the resistance can be increased, see structural calculations table, index d)
- Dowel
  - Ø8 mm, Ø10 mm and Ø12 mm, at least S235

**In concrete**

The minimum concrete encased depth for concrete encased post supports is 150 mm.

**Structural calculation tables**




**General**

The table contains characteristic values of the resistance/load-carrying capacity for determining design values in ultimate limit state. The resistances/load-carrying capacities apply to the maximum distances given in the structural calculation tables of the load application points from the top of the substrate. The verification of anchoring of the post support in the subsoil must be provided separately. In case of horizontal loading of the post support, it is recommended to verify the resistance with the lower value of the resistances F<sub>2/3</sub> and F<sub>4/5</sub>, if correct layout of the post support in the place of installation is not checked.

**Minimum and maximum distances**

Distance from top of baseplate - top of substrate, see structural calculations table **max a**  
 e<sub>2/3</sub> - maximum distance between load application - top of substrate in load case F<sub>2/3</sub>  
 e<sub>4/5</sub> - maximum distance between load application - top of substrate in load case F<sub>4/5</sub>  
 The distances e<sub>2/3</sub> and e<sub>4/5</sub> result from the distance max a and the centre of gravity of the load application for the load cases F<sub>2/3</sub> and F<sub>4/5</sub>.

$$\Sigma F_{(i,Ed)} / F_{(i,Rd)} \leq 1$$



- F<sub>1,c</sub> - compressive force (downwards) perpendicular to the baseplate
- F<sub>1,t</sub> - tensile force (upwards) perpendicular to the baseplate
- F<sub>2/3</sub> - load perpendicular to fasteners in the fin, dowel, ties
- F<sub>4/5</sub> - load parallel to fasteners in the fin, dowel, ties



„Innovationen im Holzbau“

**Resistance design value**

$$F_{i,Rd} = \min \{ k_{mod} \cdot F_{i,Rk,timber} / \gamma_{M,timber} ; F_{i,Rk,Stahl} / \gamma_{M,steel} \}$$

with  $k_{mod}$  to EN 1995-1-1 and  $\gamma_{M,timber} = 1.3$

For several connectors, 2 characteristic values are given for the steel load-carrying capacity with different partial safety factors  $\gamma_{M,steel}$ .

Both values are to be taken into consideration when determining the design value.

**Resistance analysis**

$$\sum \frac{F_{i,Ed}}{F_{i,Rd}} \leq 1$$

**Indices**

a) Resistance values apply to baseplates 8 mm and 6 mm thick.

b) Resistance values apply to a baseplate 8 mm thick. For a baseplate 6 mm thick, the values marked 1) to 6) are to be multiplied by the factor from the following table.

1)	2)	3)	4)	5)	6)
0,67	0,72	0,75	0,81	0,84	0,86

c) For tensile loading by load  $F_{1,t}$ , dowels are required in addition to the given screws.

d) If screws with threaded length  $l_{ef}$  greater than 100 mm are used, the load-carrying capacity  $F_{1,t,Rk,timber}$  can be increased by factor  $f_{1,t,timber} = (l_{ef} / 100 \text{ mm})^{0.9}$ .

Art.No.	Post		Maximum spacings			F <sub>1,c</sub> - compression			F <sub>1,t</sub> - tension			F <sub>2/3</sub>			F <sub>4/5</sub>		
	min w	min h	max a	e <sub>2/3</sub>	e <sub>4/5</sub>	Timber		Steel	Timber		Steel		Timber		Steel		
	mm	mm	mm	mm	mm	F <sub>1,c,Rk</sub>	F <sub>1,c,Rk</sub>	γ <sub>M</sub>	F <sub>1,t,Rk</sub>	F <sub>1,t,Rk</sub>	γ <sub>M</sub>	F <sub>2/3,Rk</sub>	F <sub>2/3,Rk</sub>	γ <sub>M</sub>	F <sub>4/5,Rk</sub>	F <sub>4/5,Rk</sub>	γ <sub>M</sub>
19812210	140	140	148	228	167	202,0	283	1,00	36,0	36,4	1,25	19,6	19,8	1,25	4,78	9,77	1,00

2 dowels Ø12



**zwei starke Partner!**